



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name PU 520

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Flammable liquids	Category 2 - (H225)
Eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains Methyl ethyl ketone; Acetone



SAFETY DATA SHEET

PU 520
Supercedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Signal word

Danger

Hazard statements

H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.
H225 - Highly flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P261 - Avoid breathing vapours
P280 - Wear protective gloves and eye/face protection
P273 - Avoid release to the environment
P312 - Call a POISON CENTER or doctor if you feel unwell
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Methyl ethyl ketone 78-93-3	40 - <60	01-2119457290 -43-XXXX	201-159-0 (606-002-00-3)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Acetone 67-64-1	20 - <25	01-2119471330 -49-XXXX	200-662-2 (606-001-00-8)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
1-Nitropropane 108-03-2	1 - <3	01-2119475519 -25-XXXX	203-544-9 (609-001-00-6)	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 3 (H331) Flam. Liq. 3 (H226)	-	-	-	-
Diisopropylnaphthalene 38640-62-9	1 - <2.5	01-2119565150 -48-XXXX	254-052-6	Asp. Tox. 1 (H304) Aquatic Chronic 1 (H410)	-	-	-	-
Nitroethane 79-24-3	0.1 - <1	01-2119966158 -27-XXXX	201-188-9 (609-035-00-1)	Acute Tox. 4 (H302) Acute Tox. 4	-	-	-	-

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

				(H332) Repr. 2 (H361) Aquatic Chronic 3 (H412) Flam. Liq. 3 (H226)				
--	--	--	--	--------------------------------------------------------------------------------	--	--	--	--

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	-	-	-	-	-
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
1-Nitropropane	203-544-9 (609-001-00-6)	108-03-2	455	2000	1.5	3	700
Diisopropylnaphthalene	254-052-6	38640-62-9	-	-	-	-	-
Nitroethane	201-188-9 (609-035-00-1)	79-24-3	1083	-	1.5	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

PU 520
Supercedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides. Carbon monoxide. Nitrogen oxides (NO_x). Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep from freezing.

Recommended storage temperature Keep at temperatures between 5 and 25 °C. Do not freeze.

7.3. Specific end use(s)

Specific use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*

SAFETY DATA SHEET

PU 520
 Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
 Revision Number 2.01

Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³
Nitroethane 79-24-3	TWA: 62 mg/m ³ TWA: 20 ppm STEL: 312 mg/m ³ STEL: 100 ppm *	TWA: 20 ppm TWA: 62 mg/m ³ STEL: 100 ppm STEL: 312 mg/m ³ Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	70 µmol/L - urine (Butan-2-one) - post shift
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m ³	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m ³	
Long term Systemic health effects worker	Inhalation	1210 mg/m ³	

Diisopropyl naphthalene (38640-62-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term	Dermal	4.3 mg/kg bw/d	
worker Long term	Inhalation	30 mg/m ³	

Derived No Effect Level (DNEL)			
Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	

SAFETY DATA SHEET

PU 520
 Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
 Revision Number 2.01

Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Acetone (67-64-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Diisopropylnaphthalene (38640-62-9)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Oral	2.1 mg/kg bw/d	
Consumer Long term	Dermal	2.1 mg/kg bw/d	
Consumer Long term	Inhalation	7.4 mg/m ³	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

Methyl ethyl ketone (78-93-3)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

Acetone (67-64-1)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Diisopropylnaphthalene (38640-62-9)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.236 µg/l
Marine water	0.0236 µg/l
Freshwater sediment	0.853 mg/kg dry weight
Marine sediment	0.085 mg/kg dry weight
Soil	0.171 mg/kg dry weight
Microorganisms in sewage treatment	0.15 mg/l

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Tight sealing safety goggles. Face protection shield. Eye protection must conform to standard EN 166.
Hand protection	Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Skin and body protection	Antistatic footwear. Wear fire/ flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing. Apron.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387.
Environmental exposure controls	Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Very viscous	
Colour	Colourless	
Odour	Solvent.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	= 56 °C	
Flammability	No data available	Flammable liquid
Flammability Limit in Air		None known
Upper flammability or explosive limits	13 % (V)	
Lower flammability or explosive limits	1.2 % (V)	
Flash point	-17 °C	
Autoignition temperature	343 °C	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 700 mm ² /s	@ 40°C
Dynamic viscosity	2300 - 2900 mPa s	@ 20 °C
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	
Partition coefficient	No data available	None known
Vapour pressure	<110 kPa	kPa @ 50 °C
Relative density	No data available	None known
Bulk density	No data available	
Liquid Density	0.87 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	19.80	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

SAFETY DATA SHEET

PU 520
Supercedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	15,818.90 mg/kg
ATEmix (dermal)	69,533.50 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	52.15 mg/l
ATEmix (inhalation-vapour)	104.3003 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
1-Nitropropane	=455 mg/kg (Rattus)	= 2000 mg/kg (Oryctolagus cuniculus)	=11.02 mg/L (Rattus) 1 h
Diisopropyl naphthalene	LD50 = 4130 mg/kg (Rattus) OECD 401	> 4500 mg/kg (Rattus)	>5.64 mg/L (Rattus) 4 h
Nitroethane	=1083 mg/kg (Rattus)	-	= 18.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Methyl ethyl ketone (78-93-3)			
Acetone (67-64-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitiser

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

PU 520
Supercedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					May cause drowsiness or dizziness Causes central nervous system depression

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					Narcotic effects

STOT - repeated exposure Based on available data, the classification criteria are not met.

Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour	1254, 2518, 5041 ppm/6h/d	90 days	NOAEC 5014 ppm

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/d	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/d
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
1-Nitropropane 108-03-2	EC50 72 h = 456 mg/L (Pseudokirchneriella subcapitata)	LC50 (96h) 227 mg/L (Oncorhynchus mykiss)	EC50 = 42.8 mg/L 5 min EC50 = 45.4 mg/L 15 min EC50 = 50.8 mg/L 30 min	EC50 (48h) 380 mg/L Daphnia (Daphnia magna)		
Diisopropylnaphthalene 38640-62-9	NOEC (72h) = 0.15 mg/l (Desmodesmus subspicatus) DIN 38412 part 9	>0.5 mg/l	-	EL50 (48h) = 1.7 mg/l (Daphnia magna) OECD 202		
Nitroethane 79-24-3	EC50 (72 Hr)=17.4 mg/L (Pseudokirchneriella subcapitata)	LC50 =596 mg/L (Pimephales promelas)	-	EC50 (48hr) >21.9 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Acetone (67-64-1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone	0.3
Acetone	-0.24
1-Nitropropane	0.79
Diisopropylnaphthalene	6
Nitroethane	0.162

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Methyl ethyl ketone	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
1-Nitropropane	The substance is not PBT / vPvB
Diisopropylnaphthalene	The substance is handled as if it were a PBT / vPvB
Nitroethane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The information shown here, may not always agree with the bill of lading shipping description for the material. Keep from freezing. The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition).

Land transport (ADR/RID)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (D/E)
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	640D
Classification code	F1
Tunnel restriction code	(D/E)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II, (-17°C c.c.)
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1133
14.2 UN proper shipping name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A3
Limited quantity (LQ)	1 L
ERG Code	3L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H410 - Very toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by

SAFETY DATA SHEET

PU 520
Supersedes date 05-Jan-2023

Revision date 03-Dec-2024
Revision Number 2.01

IMDG	Road
IATA	International Maritime Dangerous Goods (IMDG)
RID	International Air Transport Association (IATA)
	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Dec-2024

Indication of changes

Revision Note SDS sections updated, 8, 11, 16.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet