



Cleaner 14

CLEANER AND DEGREASER

ADVANTAGES

- Fast drying
- For heavily contaminated surfaces
- Aggressive cleaner

PRODUCT

Bostik Cleaner 14 is a thin liquid product for cleaning and degreasing substrates before sealing or bonding with specific Bostik products.

APPLICATIONS

- Cleaning and degreasing of non-porous substrates.
- Can, in specific cases, be used as adhesion improver due to deterioration of the adhesive surface.

METHOD OF USE

Rub the surfaces firmly with a clean, dye-free cloth soaked in Cleaner 14. Repeat for heavily soiled substrates.

Note: First perform a small test to ensure that the substrates will be affected by the volatile components of Cleaner 14. Plastics and lacquers, in particular, may be damaged.

Application temperature: +5 to +30 °C.

Drying time: Five minutes of drying time is recommended.

STORAGE STABILITY

Shelf life of at least 24 months in unopened original packaging when stored in a dry place at temperatures between +5 and +30 °C.

FURTHER INFORMATION

Material safety data sheet is available on bostikdsd.thewerco.com.



Technical data	
Density	0,8 g/ml
Flash point	-6°C
Article number	30022100
EAN code	871352603204
Colour	transparent
Packaging	1L tin
Packed per	6

Bostik BV

De voerman 8
5215 MH 's-Hertogenbosch
T: + 31 (0)73 6244244
infoNL@bostik.com
www.bostik.nl

BOSTIK HOTLINE

Smart help + 31 (0) 73 6 244 244
+ 32 (0) 9 255 17 17



Bostik Belux SA - NV

Meulestedekaai 86
B-9000 Gent
T: + 32 (0) 92551717
info@bostik.be
www.bostik.be