



Liquid 1

CLEANER AND DEGREASER

ADVANTAGES

- Cleaning
- Pretreating
- Does not affect surface of cladding panels
- Non-aggressive cleaner
- Suitable for tools
- Removal of fresh bituminous roof sealants



PRODUCT

Bostik Liquid 1 is a cleaning agent for cleaning surfaces, tools and particularly for the removal of fresh primer, sealant and adhesive residues or contaminants.

APPLICATIONS

- Removal of fresh primer and adhesive residues from cladding panels.
- Removal of fresh bituminous roof sealant (such as Bostik Elastorroof).

FEATURES

Non-aggressive cleaner, which normally does not affect the front of the cladding panels.

METHOD OF USE

Rub the surfaces firmly with a clean, dye-free cloth soaked in Liquid 1. Repeat for heavily soiled substrates.

Note: First perform a small test to ensure that the substrates will not be affected by the volatile components of Liquid 1. Plastics and lacquers, in particular, may be damaged.

Application temperature: +5 to +30 °C.

Drying time: Ten minutes of drying time is recommended.

STORAGE STABILITY

Liquid 1 has a shelf life of 12 months in the unopened original packaging when stored in a dry place at temperatures between +5 and +30 °C.

FURTHER INFORMATION

Material safety data sheet is available on bostikdsd.thewerco.com.

Technical data	
Chemical composition	organic solvent
Specific gravity	0.7 g/ml
Flash point	27°C
Boiling point	143°C
Ignition temperature	265°C
Drying time	10 - 15 minutes
Colour	transparent
Packaging	1 litre tin
Article code	30025380
EAN code	8713572029530
Packed per	6

BOSTIK HOTLINE

Smart help + 31 (0) 73 6 244 244
+ 32 (0) 9 255 17 17



Bostik BV

De voerman 8
5215 MH 's-Hertogenbosch
T: + 31 (0)73 6244244
infoNL@bostik.com
www.bostik.nl

Bostik Belux SA - NV

Meulestedekaai 86
B-9000 Gent
T: + 32 (0) 92551717
info@bostik.be
www.bostik.be

Bostik SA

253, avenue du Président
Wilson, 93211 La Plaine
Saint-Denis Cedex Franc
www.bostik.com

Bostik Ltd.

Common road
ST16 3EH
Stafford
www.bostik.co.uk